

Caterpillar Bulldozer D5K2 XL (2018) - Specification Sheet

General Specifications

Engine Model	Cat C4.4 ACERT, Tier 4 Final / Stage IV
Net Power	104 hp (77.6 kW) @ 2,200 rpm
Operating Weight (XL)	9,214 kg (20,313 lb)
Blade Type	VPAT / 6-Way
Blade Width	2,780 mm (109.5 in)
Blade Lift Height	767 mm (30.2 in)
Blade Digging Depth	586 mm (23.1 in)
Blade Tilt	±401 mm (15.8 in)
Ripper Type	Parallelogram, 3 shanks
Ripper Max Depth	337 mm (13.3 in)
Ripper Max Reach	556 mm (21.9 in)
Ripper Clearance	447 mm (17.6 in)
Ripper Weight	554 kg (1,222 lb)
Track Gauge (XL)	1,600 mm (63 in)
Ground Clearance	332 mm (13 in)
Length with Blade	4,309 mm (170.1 in)
Cab Height	2,769 mm (109 in)
Transport Width	2,410 mm (94.9 in)
Transmission	Hydrostatic, dual-path
Forward Speed (max)	9.0 km/h (5.6 mph)
Reverse Speed (max)	10.0 km/h (6.2 mph)
Hydraulic Pump Flow	68 L/min (17.7 gal/min)
Hydraulic Pressure	20,600 kPa (2,988 psi)
Fuel Tank Capacity	195 L (51.5 gal)
Hydraulic Fluid Capacity	59.5 L (15.7 gal)

Declaration: This specification sheet is intended for reference only. Actual machine specifications, performance, and ground conditions may differ from the information presented here. No guarantee is implied that the listed specifications will correspond exactly to any specific machine.