SANY Small Excavator SY55C (2020) - Specification Sheet

General Specifications

| Operating Weight | 5,780 kg |
|-------------------------|--|
| Engine Model | Isuzu 4JG1, 3.059 L, 36 kW @ 2,100 rpm |
| Max Torque | ≈175 Nm @ 1,800 rpm |
| Bucket Capacity | 0.21 m³ (standard); range 0.18 – 0.23 m³ |
| Bucket Digging Force | ≈45 kN |
| Boom / Stick Length | 3,000 mm / 1,550 mm |
| Max Digging Depth | 3,815 mm |
| Max Horizontal Reach | 6,090 mm |
| Dimensions (LxWxH) | 5,930 × 2,000 × 2,600 mm |
| Track Shoe Width | 400 mm |
| Ground Pressure | ≈32.75 kPa |
| Travel Speed (High/Low) | 3.73 / 2.40 km/h |
| Slewing Speed | ≈9.6 rpm |
| Fuel Tank Capacity | 130 L |
| Hydraulic Tank Capacity | 85 L |
| Radiator Capacity | 6.5 L |

Declaration: This specification sheet is intended for reference only. Actual machine specifications, performance, and ground conditions may differ from the information presented here. No guarantee is implied that the listed specifications will correspond exactly to any specific machine.